

## ALKASEAL PRIMER RESINE

### PRODUCT DESCRIPTION:

*Alkaseal Primer Resine* is an exceptional water-based acrylic copolymer latex, especially formulated to penetrate, seal and protect cementitious and concrete wall substrates.

*Alkaseal* could be used on new or previously painted surfaces as well as a base coat for all types of latex paints, granulate, texture coating.

### CHARACTERISTICS

*Alkaseal Primer Resine* possesses excellent sealing features and high alkali resistances. It could be easily applied by brush, roll or spray equipments.

*Alkaseal Primer Resine* dries to a tack-free state within one hour after application and is recoatable after four hours, depending on temperature, relative humidity and porosity of the substrate.

### SPECIFICATION DATA:

<b><u>Color:</u></b>	clear
<b><u>Viscosity:</u></b>	110 ku at 25°C.
<b><u>Density:</u></b>	1.01±0.02
<b><u>Solvent:</u></b>	water.
<b><u>Coverage:</u></b>	40 to 50 m <sup>2</sup> / 1 us gallon depending on surface Texture and porosity.
<b><u>Dry time:</u></b>	1 hour tack-free / 4 hour to recoat

### APPLICATIONS:

Exterior paints for building facades.

**STORAGE & PRECAUTIONS:**

Don't apply when surface or air temperature is below 15°C.  
Keep out of reach of children.

**PACKING:**

- 1 us Gallon                      3.785 litres.
- 5 us Gallon                      18.925 litres.