

RIDEX BRUT LATEX

FEATURES

- **Soft Satin Sheen**
- **Interior or Exterior usage**
- **Scrubbable**
- **Stain resistant**
- **Resists peeling**
- **Exceptional resistance to aging, alkali, weather and moisture**
- **Maximum durability**
- **Excellent hiding**
- **Mildew resistant**

COMPOSITION

Binder: Acrylic Modified Latex Copolymer resin specially designed for application on exterior masonry.

Pigments : a blend of Titanium dioxide and extender silicate pigments scientifically balanced for maximum hiding and exterior durability.

Thinner : water.

RECOMMENDED USES

A premium, satin finish, copolymer latex, brut color accent paint. Ideal for exterior use over properly primed masonry surfaces.

SPECIFICATION DATA

Color: Brut Cementitious color.

Finish: Satin – Matt.

Clean up Solvent: Soap and water

Density: 1.35 to 1.40

Solids: 60% by weight

Practical coverage: 40 to 50 sq.m.per gallon depending on surface texture and porosity.

Flash point: Non-flammable

Dry time: at 25° C & 50 % R.H:

Tack free ---- 1 hour

To recoat ---- 4 hours

APPLICATION

On clean and sound surface thin with water up to ½ gallon per gallon of paint and apply by brush roller or spray. For better results, a coat of RIDEX vinyl latex sealer should be applied as a primer followed by two coats of RIDEX Ext, vinyl Masonry Paint.

PRECAUTIONS & STORAGE

Do not apply when air or surface temperature is below 10° C . Stop painting at least two hours before you expect heavy dew, rain or temperature drop below 10° C .

**STORE IN ITS ORIGINAL SEALED PACKAGING
AWAY FROM DIRECT SUNLIGHT, FLAME,
HEAT AND FREEZING CONDITIONS
KEEP OUT OF THE REACH OF CHILDREN**

PACKING

- 1 us gallon (3.785 L)
- 5 us gallon (18.925 L)