

RIDEX-HYDROSEAL

FEATURES

- Colorless, non-yellowing finish.
- Provides a deep water-proofing property without changing the original colour of the stones &/or building materials.
- Prevents water absorption, thus inhibiting moulds & algae formation.
- Repels water from all absorbent building materials particularly stone, marble, granite, old and new.
- Reduces and controls damp rising from the laying foundation.
- Long lasting resistance to sunlight, atmospheric agents and alkaline.

COMPOSITION

Mixture of selected siloxane oils in hydrocarbon solvent.

RECOMMENDED USES

Impregnating agent for the protection & deep action water repellent treatment of surfaces made of stone, marble, granite, travertine, and for all absorbent building materials.

SPECIFICATION DATA

Density @ 20° C :	0.800 g/cm ³
Active agents :	8%
Flash point :	40° C
Appearance :	Liquid, clear, water white

APPLICATION

Apply as supplied with a paint brush, airless spray or roll on a suitably prepared surface free of dust, oil, grease & other contaminants.

Do not apply if rain is expected after 4 to 5 hours.

Apply sufficient quantity at following rates:

- Average 1 litre per 10 to 15 sq.m. on fairly absorbent surfaces.
- Average 1 litre per 3 to 5 sq.m. on highly absorbent surfaces.

STORAGE & PRECAUTIONS

- Use in well ventilated areas. Avoid prolonged inhalation of vapours.
- Avoid contact with eyes and skins.
- Flammable. Keep away from flames & sparks.
- In case of fire, use carbon dioxide or sand extinguishers.
- Non-toxic.
- Keep out of reach of children.

SHIPPING

Ridex-Hydroseal is packed in :

- 1US Gallon (3.785 litre)
- 5US Gallon (18.925 litre)