

EXTERIOR- INTERIOR LATEX BASE PAINT

FEATURES

- Soft satin Sheen
- Interior or Exterior Usage
- Scrubblable
- Satin
- Resistant
- Resists Peeling
- Exceptional Resistance to Aging, Alkali, Weather and Moisture
- Maximum Durability
- Excellent Hiding
- Mildew Resistant

COMPOSITION

BINDER : Acrylate Based Copolymer Resin specially designed for application on exterior masonry

PIGMENTS : A blend of Titanium Dioxide and Extender Silicate Pigments scientifically balanced for maximum hiding and exterior durability.

THINNER : Water

RECOMMENDED USES

A premium , satin finish , copolymer latex paint for interior or exterior use over properly primed masonry or previously painted surfaces.

SPECIFICATION DATA

Color	White , pale and deep accent colors.
Finish	Satin
Clean up solvent	Soap and water
Density	1.27 to 1.35 depending on colors



Solids	55% by weight (Varies with color)
Practical Coverage	40 to 50 sq. meters per gallon depending on surface
Dry time (At 25° C 50 % R.H)	Tack-Free ~ 1 hour To Recoat ~ 4 hours

APPLICATION

On clean and sound surface ,thin with water up to 50 % and apply by brush , roller or spray .

PRECAUTIONS

Do not apply when air or surface temperature is below 10° C