

RIDEX PRIMER BASE

FEATURES

- WATER BASED LATEX PRIMER
- RAPID AND SAFE APPLICATION
- SHORT SETTING TIME
- EXCELLENT ADHESION TO VIRTUALLY ALL SURFACES
- CRACK FREE, DURABLE, WEATHER RESISTANT
- SEALS EXTERIOR SURFACES OF MASONRY & CONCRETE.
- PROVIDES TEETH TO SUBSEQUENT RIDEX TEXTURE COATINGS.
- HIGHLY RESISTENT TO ALKALINE SUBSTRATES.

COMPOSITION

Ridex Primer Base is an acrylate based latex sealer modified with extremely durable prime pigments, extender fillers and adhesion promoting additives.

RECOMMENDED USES

Ridex Prime Base Coating is an interior-exterior high build latex coating destined to seal & prime surfaces for subsequent texture coating applications.

SPECIFICATION DATA

Color: White. Special tailor made colors are available on request.

Finish: smooth flat

Solvent : water

Practical coverage: from 100 to 120 sq.m. per 5 us gallons depending on surface porosity & method of application.

Dry time : at 25° C and 50% R.H.:

To touch ---- 2 hours

To recoat ---- overnight

Shelf Life: over one year under proper storage conditions

Specific Gravity: 1.60 ± 0.1

Solids Percentage: 75% ±1 by weight

Solids Percentage: 60% ±1 by volume

Consistency: ≥ 140 K.U. at 25° C Highly Thixotropic

SURFACE PREPARATION

All surfaces must be clean, dry and free of oil, grease, dirt, curing compounds, mildew and other foreign matters.

NEW CONCRETE , MASONRY

Remove loose aggregate. Thin *Ridex Primer Base* as desired and up to 40%. Prime & seal surface using longhaired lambwool roller. Allow to dry overnight before final coat application.

PREVIOUSLY PAINTED SURFACES

Remove heavy chalky residues by scrubbing with water and detergent and rinse clean. Remove all loose paint back to sound surface. Prime chalky areas with *Ridex Prime* water base sealer. Allow to dry overnight before final coat application.

MIXING AND THINNING

Mix thoroughly and thin up to 40% with clean water as required.

APPLICATION

Apply *Ridex Primer Base Coating* using long haired lambwool roller or suitable brush if necessary.

CLEAN UP

Wipe up drips and spatters with cloths wet with soap and water.

Clean all equipments with warm , soapy water.

PRECAUTIONS & STORAGE

STORE IN ITS ORIGINAL SEALED PACKAGING AWAY FROM DIRECT SUNLIGHT, FLAME, HEAT AND FREEZING CONDITIONS

DO NOT APPLY WHEN TEMPERATURE OF AIR OR SURFACE IS BELOW 15° C OR WHEN FOG OR RAIN IS EXPECTED TO OCCUR DURING THE FIRST STAGE OF THE DRYING PERIOD.

KEEP OUT OF REACH OF CHILDREN.

PACKING

5 us gallons