

# RIDEX ROLL TEXTURE

## FEATURES

- AVAILABLE IN FINE AND COARSE TEXTURES
- WATER BASED COATING, SELFPRIMING
- RAPID AND SAFE APPLICATION
- SHORT SETTING TIME
- EXCELLENT ADHESION TO VIRTUALLY ALL SURFACES
- CRACK FREE, DURABLE, WEATHER RESISTANT
- HIDES ROUGH OR IRREGULAR SURFACES IN JUST ONE SINGLE COAT

## COMPOSITION

*Ridex Roll Texture Coating* is a acrylate based copolymer emulsion modified with extremely durable prime pigments, extender fillers and texture additives.

## RECOMMENDED USES

*Ridex Roll Texture Coating* is an interior-exterior high build latex texture coating destined to uniform and beautify rough or irregular surfaces in just one coat over suitability primed substrate.

*Ridex Roll Texture Coating* is recommended for use on interior or exterior surfaces of masonry, concrete, wood, block-walls and cement asbestos. It is especially used to provide a uniform texture appearance to rough and irregular surfaces.

*Ridex Roll Texture Coating* is available in fine and coarse textures.

## SPECIFICATION DATA

**Color:** White and ready mix colors. Special tailor made colors are available on request.

**Finish:** flat

**Solvent:** water

**Recommended Film Thickness:** from 1.5 to 2.5 mm dry film

**Practical coverage:** from 20 to 25 sq.m. per 5 us gallon depending on surface porosity, method of application and texture requirement

**Dry time** : at 25° C and 50% R.H.:

To touch	---	2 hours
----------	-----	---------

Full hardness	---	7 days
---------------	-----	--------

**Shelf Life** : over one year under proper storage conditions

## SURFACE PREPARATION

All surfaces must be clean, dry and free of oil, grease, dirt, curing compounds, mildew and other foreign matters.

#### NEW CONCRETE, MASONRY

Remove loose aggregate. Use *Ridex Primer Base* or *Ridex Roll Texture Coating, thinned up to 25% with water*, as a primer sealer over new concrete or masonry. Prime using longhaired lambwool roller. Allow to dry overnight before final coat application.

#### PREVIOUSLY PAINTED SURFACES

Remove heavy chalky residues by scrubbing with water and detergent and rinse clean. Remove all loose paint back to sound surface. Prime chalky areas with *Ridex* solvent based penetrating sealer. Allow to dry overnight before final coat application.

#### MIXING AND THINNING

Mix thoroughly and thin only if necessary up to 2 % of water per 5 us gallon.

#### APPLICATION

Apply *Ridex Roll Texture Coating* over suitability primed surface using a sponge roller of coarse or fine textured surface.

#### CLEAN UP

Wipe up drips and spatters with cloths wet with soap and water.

Clean all equipments with warm, soapy water.

#### PRECAUTIONS & STORAGE

STORE IN ITS ORIGINAL SEALED PACKAGING AWAY FROM DIRECT SUNLIGHT, FLAME, HEAT AND FREEZING CONDITIONS.

DO NOT APPLY WHEN TEMPERATURE OF AIR OR SURFACE IS BELOW 15° C OR WHEN FOG OR RAIN IS EXPECTED TO OCCUR DURING THE FIRST STAGE OF THE DRYING PERIOD.

KEEP OUT OF REACH OF CHILDREN.

#### PACKING

- 5 us gallon