

ALKASEAL PRIMER SEALER

PRODUCT DESCRIPTION

ALKASEAL Primer Sealer is an exceptional water-based acrylic copolymer copolymer latex especially formulated to penetrate, seal and protect cementitious and concrete wall substrates.

ALKASEAL Primer Sealer could be used on new or previously painted surfaces as well as a base coat under all types of alkyd, oil and latex paints

CHARACTERISTICS

ALKASEAL Primer Sealer possesses excellent sealing features and high alkali resistance. It could be easily applied by brush, roll or spray equipments.

ALKASEAL Primer Sealer dries to a tack-free state within one hour after application and humidity and porosity of the substrate.

SPECIFICATION DATA

COLOR	CLEAR, MILKY OR WHITE. ALSO AS PER CUSTOMERS REQUEST
SOLIDS	28% BY WEIGHT
VISCOSITY	110 KU AT 25° C
DENSITY	1.01 ± 0.02
CLEAN-UP SOLVENT	WATER
COVERAGE	60 TO 70M ² / 1 US GALLON DEPENDING ON SURFACE TEXTURE AND POROSITY
DRY TIME	1 HOUR TACK-FREE. 4 HOURS TO RECOAT

SURFACE PREPARATION AND APPLICATION

All surfaces should be sound, clean and free of oil, grease, loose paint or any foreign materials. Thin with water up to 50% or as suitable. Apply by brush , roller or spray

PRECAUTIONS

Don't apply when surface or air temperature is below 15° C.

Keep out of reach of children.

PACKING

- 1 US GALLON 3.785 LITRES
- 5 US GALLON 18.925 LITRES