

RIDEX SANTEX

CHARACTERISTICS

- Beautifies and decorates rough and irregular exterior-interior surfaces in one coat!
- Possess very good adherence to dry cemented surfaces, excellent flexibility, durability, water and weathering resistance.
- Provides rapid application together with a short setting time. Color stable.
- Resist to all atmospheric conditions
- Ridex Santex is an impermeable yet breathable finish.

COMPOSITION

Ridex Santex is an acrylate based copolymer synthetic resin modified with granulated colored marble of wide range of colors and stabilized with appropriate additives for long term protection.

RECOMMENDED USE

Ridex Santex is a high build decorative coating for use on interior or exterior surfaces of masonry, concrete block walls, etc... in order to provide a beautiful protective finish to otherwise rough and irregular surfaces. Available in wide colored marbled grains of 1.0 mm to 1.25 mm average size.

SPECIFICATION DATA

Color	Ready mix colors, custom tailor made colors
Clean up	Soap and water
Recommended Film thickness	1.5 mm dry film

Practical coverage	From 8 to 10 square meters per 5 us gallons of 25 kg net weight depending on surface
Consumption	Average 2.5 to 3.0 kg/square meters
Flash point	Non-flammable
Dry time	@ 25°C and 50% R.H. To touch ----- 2 to 3 hours Full hardness ----- one week

SURFACE PREPARATION AND APPLICATION METHOD

- All surfaces must be clean, dry and free of oil, grease, dirt and curing compounds
- Apply Ridex Primer .Allow overnight drying before applying Ridex Santex using a stainless steel trowel
- Smooth the surface using same tool (stainless steel trowel)

STORAGE & PRECAUTIONS

- Store in its original sealed packaging away from direct sunlight, flame, heat and freezing conditions
- Do not apply when temperature of air or surface is below 15°C
- Keep out of reach of children

PACKING

5 us gallon pail of 25 kg net